

Foundation

CLASSIFICATION:

- Modified acrylic floor sealer finish

PACKAGING:

Jug	Pail	Drum
4L	18.9L	210L

DESCRIPTION:

- **Foundation** Sealer Finish may be used as a base coat for any floor that is maintained with a floor finish system. It may also be used as a one product system.
- **Foundation** Sealer Finish acts as a pore sealer for worn or porous floors such as terrazzo / rubber and concrete.
- **Foundation** Sealer Finish provides excellent adhesion characteristics on substrates showing adhesion sensitivity (e.g. semi-porous quarry tile and rubber).
- **Foundation** Sealer Finish is removable with conventional floor strippers.
- **Foundation** Sealer Finish is completely white in both liquid and dried forms, undergoing no yellowing / discolouration caused by age or uv light.

CHEMICAL AND PHYSICAL PROPERTIES:

- Appearance White opaque liquid
- Odour Mild acrylic + ammonia
- pH 8 – 9
- Specific Gravity 1.02
- Viscosity Less than 20 cps
- Nonvolatiles / Solids 20%

USE DIRECTIONS:

- **Application:** Prepare floor by scrubbing with a Sanilabs neutral cleaner or Sanilabs Tuff-Scrub, or by stripping with a Sanilabs stripper according to label directions. Rinse well. Apply **Foundation** Sealer Finish undiluted in uniform coats (35-75 m²/L; 1500-3000 ft²/ US gal) with a clean floor finish string mop or flat mop. Allow adequate dry time between coats (30 minutes minimum, or 15 minutes after dry to touch, whichever is longer). Any other Sanilabs floor finish may be applied over **Foundation** Sealer Finish.
- **Maintenance:** Dust mop and clean daily using a Sanilabs neutral cleaner or maintainer. If used as a one product system, **Foundation** Sealer Finish may be Burnished (1500-3000 rpm) using a light synthetic / natural hair blend pad.

See Material Safety Data Sheet for proper handling and safety instructions.